




The LR 1200 convinces with high performance and very compact design. Lifting capacities up to 220 tonnes are possible thanks to its particularly solid boom and jib system. Neptune Marine offers turnkey crawler cranes, available for charter on various pontoons.

INFORMATION	
BRAND	Liebherr
ТҮРЕ	LR 1200
BOOM LENGTH	20-62 meters
AUXILIARY JIB	Runner
WINCHES	2 x (rope Ø 26 mm)
LINE PULL	12 tons (120 kN)
ENGINE	Liebherr 230 kW (308 HP) Tier IV F
OPERATING WEIGHT	+/- 210 T (Basic boom 20 m)
FEATURES	
A/C	Yes
SELF-ERECT	Yes
FREE-FALL ON WINCHES	Optional
CAMERA	Yes
TRACKS	Flat pads tractor type 1200 mm



Load capacities with main boom

Load capacities in [t] with 82.3 t rear counterweight and 36 t carbody counterweight

		Boom length [m]											
		20	26	32	38	44	50	56	62	68	74	80	89
	6					114.8							
	7				129.5	107.8	90.1	80.2	65.4				
	8		141.2	132.6	118.8	100.9	83.7	77.6	64.9	52.0	45.0		
	9	129.7	122.8	116.0	109.8	93.2	78.8	74.8	62.1	50.3	44.7	37.0	26.6
	10	114.2	108.5	103.0	98.0	87.2	73.6	71.9	60.2	48.3	43.1	36.0	26.6
	14	70.5	70.5	70.5	67.7	65.2	59.2	60.4	52.3	41.4	38.1	31.7	24.0
	20	43.3	43.5	43.5	43.2	43.0	42.4	41.0	39.5	33.7	32.6	27.0	20.4
	22		38.3	38.3	38.0	37.8	37.5	36.7	35.5	32.0	31.1	25.6	19.4
Radius [m]	24		34.0	34.0	33.8	33.6	33.3	33.0	32.0	30.2	29.8	24.5	18.5
lius	26		30.4	30.5	30.3	30.1	29.8	29.5	29.1	28.1	27.1	23.5	17.7
Rac	32			22.8	22.7	22.5	22.1	21.9	21.5	21.2	20.7	19.9	16.1
	38				17.5	17.4	17.1	16.8	16.5	16.2	15.8	15.4	14.3
	44					13.8	13.5	13.3	12.9	12.6	12.2	11.9	11.1
	46						12.5	12.3	12.0	11.7	11.3	10.9	10.3
	48						11.7	11.5	11.1	10.8	10.4	10.1	9.4
	50						10.9	10.6	10.3	10.0	9.6	9.2	8.7
	55							8.8	8.5	8.2	7.8	7.5	6.9
	60								7.0	6.7	6.4	6.0	5.5
	65									5.5	5.1	4.8	4.3
	70										4.1	3.7	3.2
	75											2.8	2.3

Load capacities in [t] with 72.3 t rear counterweight and 36 t carbody counterweight

		Boom lengh [m]											
		20	26	32	38	44	50	56	62	68	74	80	89
	4.1	219.1											
	5	216.9	162.8	153.6									
	6	194.3	159.0	150.7	140.3	114.8							
	7	164.9	152.5	141.8	129.5	107.8	90.1	80.2	65.4				
	8	138.9	129.8	121.8	114.5	100.9	83.7	77.6	64.9	52.0	45.0		
	9	119.8	112.8	106.5	100.8	93.2	78.8	74.8	62.1	50.3	44.7	37.0	26.6
	16	53.7	53.7	53.6	53.3	51.4	49.5	47.7	45.9	38.8	36.2	29.9	22.5
	18	45.7	45.7	45.7	45.5	45.0	43.4	41.9	40.4	36.0	34.3	28.5	21.3
Ξ	20	39.5	39.6	39.6	39.4	39.2	38.5	37.2	35.8	33.7	32.6	27.0	20.4
Radius [m]	26		27.6	27.7	27.4	27.2	26.9	26.6	26.2	25.2	24.3	23.3	17.7
Rad	28			24.9	24.7	24.5	24.2	23.9	23.6	23.0	22.0	21.2	17.1
	32			20.5	20.4	20.2	19.9	19.6	19.2	18.9	18.4	17.6	16.1
	34				18.6	18.5	18.1	17.9	17.5	17.2	16.8	16.1	14.8
	40					14.3	14.0	13.7	13.4	13.1	12.7	12.3	11.3
	46						11.1	10.8	10.5	10.2	9.8	9.4	8.6
	48						10.2	10.0	9.6	9.3	8.9	8.6	7.9
	50						9.5	9.2	8.9	8.6	8.2	7.8	7.2
	55							7.6	7.3	6.9	6.6	6.2	5.7
	60								5.9	5.6	5.2	4.9	4.3
	65									4.4	4.1	3.7	3.2
	70										3.1	2.8	2.2

Liebherr LR 1200-1 | Crawler crane

For more information, please contact us on: T +31 (0)184 621 423 E info@neptunemarine.com W www.neptunemarine.com Version: V.02

