







The LR 1400 SX convinces with high performance and very compact design. Lifting capacities up to 220 tonnes are possible thanks to its particularly solid boom and jib system. Neptune Marine offers turnkey crawler cranes, available for charter on various pontoons.

INFORMATION						
BRAND	Liebherr					
TYPE	LR 1400 SX					
BOOM LENGTH	74 meters					
AUXILIARY JIB	Runner					
WINCHES	2x					
LINE PULL	Max. 2 x 223 kN					
ENGINE	Liebherr 450 kW, stage V + Tier 4F					
OPERATING WEIGHT	Approx. 353.7 t					
FEATURES						
A/C	Yes					
SELF-ERECT	Yes					
FREE-FALL ON WINCHES	Yes					
CAMERA	Yes					
TRACKS	Yes					









## Load capacities with main boom

l nad	capacities in	m
Lucu	capacities iii	1.4

roa	Load capacities in [t]												
													95
-	4.9	400.0°	40	92		90	20	02	99		00	07	773
	6	351.0	348.2	345.7									
	7	304.9	301.1	299.9	289.7	265.9							
-	8	266.6	265.9	263.1	257.4	255.0	242.1	203.7					
	9	239.7	236.9	235.5	231.6	226.9	222.1	200.8	179.8	158.2			
	10	215.6	213.3	212.7	207.5	205.8	202.4	189.5	175.1	157.4	143.3	119.5	
	11	195.8	195.7	192.7	189.0	186.2	184.6	177.3	169.5	152.4	141.2	119.5	106.0
	14	153.0	153.1	152.0	148.2	146.8	143.4	137.8	132.6	127.5	122.7	113.5	102.2
_	17	122.0	122.1	122.0	121.1	119.5	115.9	111.7	107.7	103.8	100.1	94.7	91.2
	20	97.5	97.8	97.7	96.7	96.1	95.5	93.1	89.9	86.7	83.6	79.1	76.2
	22		85.9	85.9	84.9	84.2	83.6	83.0	80.6	77.3	74.9	70.8	68.2
_	24		76.4	76.4	75.4	74.7	74.1	73.4	72.7	70.1	67.6	63.8	61.3
	26		68.5	68.6	67.6	66.9	66.3	65.6	64.9	63.6	61.2	57.8	55.5
	28			62.0	61.1	60.4	59.8	59.0	58.3	57.6	55.8	52.5	50.3
-	30			56.4	55.6	54.9	54.2	53.5	52.8	52.0	51.0	47.9	45.8
	32 34			51.6	50.8 46.7	50.1 46.0	49.5 45.3	48.7 44.6	48.0 43.8	47.2 43.0	46.5 42.3	43.8 40.2	41.8 38.3
	36				43.0	42.3	41.7	40.9	40.2	39.4	38.7	36.9	35.1
-	38				39.8	39.1	38.5	37.7	37.0	36.2	35.4	34.0	32.2
	40				36.9	36.3	35.6	34.8	34.1	33.3	32.6	31.3	29.6
T	42				34.3	33.7	33.1	32.3	31.6	30.8	30.0	28.8	27.2
Radius [m]	44				31.9	31.4	30.8	30.0	29.3	28.4	27.7	26.5	25.0
충	46				04.7	29.2	28.6	27.9	27.2	26.3	25.6	24.4	23.0
œ	48					27.3	26.7	26.0	25.2	24.4	23.6	22.3	21.1
-	50					25.4	25.0	24.2	23.5	22.7	21.8	20.4	19.4
	52						23.3	22.6	21.9	21.0	20.1	18.7	17.7
	54						21.8	21.1	20.4	19.4	18.6	17.1	16.1
_	56						20.4	19.7	19.0	18.0	17.1	15.8	14.8
	58							18.4	17.6	16.6	15.8	14.4	13.4
_	60							17.1	16.3	15.5	14.6	13.2	12.2
	62							15.9	15.2	14.3	13.4	12.0	11.0
	64								14.1	13.2	12.3	10.9	9.9
_	66								13.0	12.1	11.2	9.9	8.8
	68								12.0	11.1	10.3	8.9	7.9
	70 72									10.2 9.3	9.4 8.5	8.0 7.1	7.0 6.1
-	74									8.4	7.6	6.3	5.3
	76									0.4	6.8	5.5	4.5
	78										6.1	4.8	3.8
	80										5.4	4.1	3.1
	82											3.4	
	83											3.1	
	84											2.8	
	86											2.1	
	86.4											2.0	
	_	y lift configura	tion										

with heavy lift configuration

Carbody counterweight: 52.6 t with 1500 mm flat track pads

100.5 t 140.9 t 120.5 t 150.9 t



## Liebherr LR 1400 SX

