



Neptune


The LR 1400 SX convinces with high performance and very compact design. Lifting capacities up to 400 tonnes are possible thanks to its particularly solid boom and jib sys-tem. Neptune Marine offers turnkey crawler cranes, available for charter on various pontoons.


Liebherr LR 1400 SX | Crawler crane

INFORMATION	
BRAND	Liebherr
ТҮРЕ	LR 1400 SX
BOOM LENGTH	74 meters
AUXILIARY JIB	Runner
WINCHES	2x
LINE PULL	Max. 2 x 223 kN
ENGINE	Liebherr 450 kW, stage V + Tier 4F
OPERATING WEIGHT	Approx. 353.7 t
FEATURES	
A/C	Yes
SELF-ERECT	Yes
FREE-FALL ON WINCHES	Yes
CAMERA	Yes
TRACKS	Yes









	Boom length [m]											
	20	26	32	44	50	56	62	68	74	80	89	95
4.9	400.0*											
6	351.0	348.2	345.7									
7	304.9	301.1	299.9	289.7	265.9							
8	266.6	265.9	263.1	257.4	255.0	242.1	203.7					
9	239.7	236.9	235.5	231.6	226.9	222.1	200.8	179.8	158.2		110.5	
10	215.6	213.3	212.7	207.5	205.8	202.4	189.5	175.1 169.5	157.4	143.3	119.5	10/ 0
14	195.8	153.1	152.0	169.0	166.2	184.0	177.5	132.6	152.4	141.2	119.5	106.0
17	103.0	155.1	152.0	140.2	119.5	115.9	137.8	107.7	103.8	100.1	94.7	91.2
20	97.5	97.8	97.7	96.7	96.1	95.5	93.1	89.9	86.7	83.6	79.1	76.2
22	11.4	85.9	85.9	84.9	84.2	83.6	83.0	80.6	117	74.9	70.8	68.2
24		76.4	76.4	75.4	74.7	74.1	73.4	72.7	70.1	67.6	63.8	61.3
26		68.5	68.6	67.6	66.9	66.3	65.6	64.9	63.6	61.2	57.8	55.5
28			62.0	61.1	60.4	59.8	59.0	58.3	57.6	55.8	52.5	50.3
30			56.4	55.6	54.9	54.2	53.5	52.8	52.0	51.0	47.9	45.8
32			51.6	50.8	50.1	49.5	48.7	48.0	47.2	46.5	43.8	41.8
34				46.7	46.0	45.3	44.6	43.8	43.0	42.3	40.2	38.3
36				43.0	42.3	41.7	40.9	40.2	39.4	38.7	36.9	35.1
38				39.8	39.1	38.5	37.7	37.0	36.2	35.4	34.0	32.2
40				36.9	36.3	35.6	34.8	34.1	33.3	32.6	31.3	29.6
42				34.3	33.7	33.1	32.3	31.6	30.8	30.0	28.8	27.2
44				31.9	31.4	30.8	30.0	29.3	28.4	27.7	26.5	25.0
46					29.2	28.6	27.9	27.2	26.3	25.6	24.4	23.0
48					27.3	267	26.0	25.2	24.4	23.6	22.3	21.1
50					25.4	25.0	24.2	23.5	22.7	21.8	20.4	19.4
52						23.3	22.6	21.9	21.0	20.1	18.7	17.7
54		<u> </u>	L	<u> </u>	L	21.8	21.1	20.4	19.4	18.6	17.1	16.1
56						20.4	19.7	19.0	18.0	17.1	15.8	14.8
58 60							18.4	17.6	16.6	15.8	14.4 13.2	13.4
		<u> </u>		<u> </u>	<u> </u>		17.1		15.5	14.6		12.2
62 64							12.9	15.2	14.3 13.2	13.4	12.0 10.9	11.0
66								13.0	12.1	11.2	9.9	8.8
68		<u> </u>		<u> </u>			<u> </u>	12.0	111	10.3	8.9	7.9
70								12.0	10.2	9,4	8.0	7.0
72									9.3	8.5	7.1	6.1
74									8.4	7.6	6.3	5.3
76										6.8	5.5	4.5
78										6.1	4.8	3.8
80										5.4	4.1	3.1
82											3.4	
83											3.1	
84											2.8	
86											2.1	
86.4											2.0	

Load capacities with main boom

Load capacities in [t]

• with heavy lift configuration

Carbody counterweight: 52.6 t with 1500 mm flat track pads Rear counterweight: 100.5 t 140.9 t 150.9 t



Liebherr LR 1400 SX |

